

## REPLACEMENT VACUUM INTERRUPTER

### Specifications and Ratings

| Contactor/Breaker Type         | Rated Current (A rms) | Max Voltage (kV rms) | Impulse Withstand (kV peak) | Rated Short Circuit Amps (kA) |
|--------------------------------|-----------------------|----------------------|-----------------------------|-------------------------------|
| HYUNDAI VACUUM CIRCUIT BREAKER | 2000                  | 17.5                 | 95                          | 31.5                          |

### Standard Features and Options

- IMPULSE TESTED TO ANSI C37
- AC WITHSTAND TEST TO ANSI C37
- EXCELLENT HIGH VOLTAGE INSULATION
- HIGH CUMULATIVE AND HIGH BREAKING CAPACITY
- ULTRA-SMALL AND LIGHT-WEIGHT
- HIGH RELIABILITY DUE TO STRINGENT TESTING
- FINE-ALUMINA CERAMIC FOR EXCELLENT VACUUM SEAL
- Cu-Cr CONTACT FOR EXCELLENT HIGH VOLTAGE CONDUCTIVITY AND BREAKING PERFORMANCE
- EXCLUSIVE INTERNAL TORSION CONTROL
- FULL 1-YEAR WARRANTY

### Typical Dimensions

